

US005317323A

United States Patent [19]

Kennedy et al.

[11] Patent Number:

5,317,323

[45] Date of Patent:

May 31, 1994

[54]	PASSIVE HIGH ACCURACY GEOLOCATION
	SYSTEM AND METHOD

[75] Inventors: Joseph P. Kennedy, Fairfax;

Christopher D. Roller, Burke; Robert

W. Hooper, Arlington, all of Va.

[73] Assignee: E-Systems, Inc., Dallas, Tex.

[21] Appl. No.: 26,782

[56]

[22] Filed: Mar. 5, 1993

[51] Int. Cl.⁵ G01S 3/02

[52] U.S. Cl. 342/457; 342/357; 342/465

References Cited

U.S. PATENT DOCUMENTS

3,996,590	12/1976	Hammack .	
4,494,119	1/1985	Wimbush	342/457
4,740,792	4/1988	Sagey et al	342/457
4,742,357	5/1988	Rackley	342/457
4,791,572	12/1988	Green, III et al	342/457
4,797,679	1/1989	Cusdin et al	342/387

4,884,208	11/1989	Marinelli et al	342/351
4,888,593	12/1989	Friedman et al	342/387
4,916,455	4/1990	Bent et al	342/457
5.008.679	4/1991	Effland et al	342/353

Primary Examiner—Theodore M. Blum Attorney, Agent, or Firm—Rogers & Killeen

[57] ABSTRACT

A system for accurately locating a mobile cellular radio includes plural radio receivers, the position of each being precisely known, a satellite-based time source for providing the actual time of arrival of a radio signal at the plural radio receivers, and a device for removing multipath and cochannel interference from the received signals so that actual time of arrival of the radio signal may be determined accurately. The Global Positioning System (GPS) may be used to provide the time signal and to provide the precise location of the plural radio receivers. The system may be used to passively determine the location of the mobile radio and is accurate enough to use with a computer generated map system.

31 Claims, 6 Drawing Sheets

